



Artistic Nail Design: 03001 - Avante Garde, 03002 - Contempo, 03003 - Fashionista, 03004 - Diva Chic, 03005 - Glam, 03006 - Eccentric, 03007 - Metro, 03008 - Cheeky, 03009 - Foxy, 03010 - Fab, 03011 - Flashing, 03012 - Das ing, 03013 - Trendy, 03014 - Trist, 03015 - Posh, 03016 - Swanky, 03017 - Uptown, 03018 - All the Rage, 03019 - Vc 03020 - Sooo In, 03021 - Fierce, 03022 - Innocence, 03023 - Angels, 03024 - Precious, 03025 - Lucious, 03026 - Seductive, 03027 - Lovely, 03028 - Lovely, 03029 - Karma, 03030 - Halo, 03031 - Dazzled, 03032 - Bling Bling, Illusion, 03040 - Caffeine, 03041 - Mocha Chino, 03042 - Java Java, 03043 - Café Latté, 03044 - Naked. 03045 - Glisten, 03046 - Peach Whip, 03047 - La-Ti-Da, 03048 - Sassy, 03049 - Muse, 03050 - Misstep, 03051 - Deblu, 03052 - Tease, 03053 - With It, 03054 - Frenzy, 03055 - Wham, 03056 - Fly, 03057 - Crazyed, 03058 - Hotzy, 03059 - Juiced, 03060 - Glowing, 03061 - Vivid, 03062 - Hype, 03063 - Owned. 03064 - Manic, 03065 - Psyched, 03066 - Toxic, 03067 - Royalty, 03068 - Sovereign, 03069 - Imperial, 03070 - Majestic, 03071 - Luxe, 03072 - Nobility

Material Safety Data Sheet

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: Artistic Colour Gloss
Chemical Name: N/A

MSDS Prepared By:
MSDS Initial Approval Date: 9/1/2010

Family: Artistic Colour Gloss

Manufacture: Artistic Nail Design
14509 Best Ave unit B Norwalk, Ca 90650

Product Use:
Product #: Multiple Colour Gloss - Soak Off Gel Polish

Emergency Phone Number: (800) 535-5053
Information Contacts: (714)635-5110

Section 2: Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- May be slightly toxic.
• May cause moderate skin injury (reddening & swelling).
• May cause eye irritation

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: No specific information available. Although, this product opposes only slight irritation concern with all routes of entry.
Eye: No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation
Skin: No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.
Ingestion: No specific information available. Contains materials that may be practically nontoxic.
Inhalation: No specific information available. Low volatility makes vapor inhalation unlikely.
Sub-Chronic Effects: No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section II, Toxicological Information for Details

Section 3: Composition/Information on Ingredients

Table with 8 columns: Chemical Identity, CAS#, EINECS#, INCI Name, Exposure OSHA TWA/STEL, Limits ACGIH TWA/STEL, Carcinogen IARC/NTP/OSHA, %

Black Iron Oxide	12227-89-3	235-442-5	Black Iron Oxide	N/E	N/E	Not Listed
Red Iron Oxide	51274-00-1	257-098	Red Iron Oxide	N/E	N/E	Not Listed
D&C Red #7	5858-81-1	227-497-9	D&C Red #7	N/E	N/E	Not Listed
D&C Red #34	6417-83-0	229-142-3	D&C Red #34	N/E	N/E	Not Listed
N/E - None Established N/R - Not Reviewed	N/DA - No Data Available N/A - Not Applicable		* See section 16			

Di-Hema Trimethylhexyl Dicarbamate	Hazard Symbol: Xi	Risk Phrases: R36/37/38	Safety Phrases: S14, S3/7, S62
Butyl Acetate	Hazard Symbol: Xi	Risk Phrases: R36/38, R43	Safety Phrases: S2, S26
Ethyl Acetate	Hazard Symbol: Xi	Risk Phrases: R36/38, R43	Safety Phrases: S2, S26
2-Hydroxy ethyl methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36/38, R43	Safety Phrases: S2, S26, S28
Hydroxypropyl Methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36//37/38, R43	Safety Phrases: S26, S36/37
Isobomyl Methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36/37/38	Safety Phrases: S26,S27,S28,S29,S30,S33,S35,S36

See Section 16 for Risk and Safety Phrase Key

#### Section 4: First Aid Measures

First Aid for Eye	Flush with plenty of water for 15 minutes and retract eyelids often. Seek medical attention immediately.
First Aid for Skin	Remove contaminated clothing and wash contact area with soap and water for 15 minutes.
First Aid for Inhalation	In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.
First Aid for Ingestion	If appreciable quantities are swallowed, seek medical attention.

#### Section 5: Fire Fighting Measures

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
>212 °F/100 °C Seta flash	No Data	No Data

##### Method:

Extinguishing Media:	Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.
Unusual Hazards:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

#### Section 6: Accidental Release Measures

Spill or Release Producers:	Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detergent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.
-----------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### Section 7: Handling and Storage

Handling:	Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential.  Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheating of product, this will also diminishing the quality of the product.
Storage:	Product is extremely light sensitive. If exposed to natural light, LED, UVA, UVB or UV any light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.
Explosion Hazard:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

#### Section 8: Exposure Controls / Personal Protection

Engineering Controls	Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.
----------------------	------------------------------------------------------------------------------------------------------------------------------------------

## Personal Protective Equipment

General: To identify additional Personal protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron boots, or whole body suits. Nitrile rubber is better than PVC.

Eye / Face Protection: Wear chemical splash goggles

Skin Protection: Wear impervious gloves (Neoprene)

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

## Section 9: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	%Volatile
Clear to slight violet, viscous liquid	characteristic acrylate odor	NA	(H2O=1): 1.15	N/DA	By Volume: <0.5

Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure: (mm Hg) @ 20 C:<0.01	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A		No Data	No Data	No Data	Insoluble

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
>212 °F/100 °C Seta flash	No Data	No Data

## Section 10: Stability and Reactivity

Stability	Incapability (Material to Avoid):
Normally Stable	Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.
<b>Hazardous Decomposition Products:</b> Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide	<b>Hazardous Polymerization:</b> May occur --- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.
<b>Conditions to Avoid:</b> Storage<100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization, contamination with incompatible materials.	

## Section 11: Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No info available	No info available	No info available	No info available	No info available

Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA

## Section 12: Ecological Information

### Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

### Chemical Fate Information

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

## Section 13: Disposal Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations. Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

## Section 14: Transport Information

### DOT (49 CFR 172)

Proper Shipping Name: Non-Regulated Material  
Identification Number: N/A  
Marine Pollutant: No  
Special Provisions: N/A  
Emergency Response Guidebook (ERG) #: N/A

**IATA (DGR):**

Proper Shipping Name: Non-Regulated Material  
 Class or Division: N/A  
 UN or ID Number: N/A  
 Packaging Instructions:

**Emergency Response Guidance (ICAO)#:****IMO (IMDG):**

Proper Shipping Name: Non-Regulated Material  
 Class or Division: N/A  
 UN or ID Number: N/A  
 Special Provisions & Stowage/Segregation: None

**Emergency Schedule (EmS)#:**

**Other Information:** Flash point >100 °C

**Section 15: Regulatory Information****US Federal Regulations**

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: <ul style="list-style-type: none"> <li>• NONE</li> </ul> This product contains no ODS's
Clean Water Act: Priority Pollutant	This product contains no chemicals listed under the U.S. Clean Water Act Priority Pollutant List
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazard are: <ul style="list-style-type: none"> <li>• Immediate (acute) health hazard</li> <li>• Delayed (chronic) health hazard</li> <li>• Reactive hazard</li> </ul>
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261)
SARA Title III: Section 302 (TPQ)	This product contains the following chemicals regulated under Sec. 302 as extremely hazardous substance that carry a TPQ. <ul style="list-style-type: none"> <li>• NONE</li> </ul>
SARA Title III: Section 304	This product contains the following chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification ("CERCLA" List):
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> <li>• Immediate (acute) health hazard</li> <li>• Delayed (chronic) health hazard</li> <li>• Reactive hazard</li> </ul>
SARA Title III: Section 313:	This product contains the following chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
TSCA Section 8(b) Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.


**State Regulations**

CA Right-to-Know Law:	NONE
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	NONE
NJ Right-to-Know Law:	NONE
PA Right-to-Know Law:	NONE
FL Right-to-Know Law:	NONE
MN Right-to-Know Law:	NONE

**International Regulations**

CDSL: Canadian Inventory (on Canadian Transitional List)	Hydropropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS - n/da 2-Hydroxyethyl methacrylate CASE# 868-77-9 is on the DSL List. WHMIS - n/da Isobornyl Methacrylate CAS# 7534-94-3 is on the DSL list. WHMIS - n/da
----------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Labeling according to EC Directives - 1999/45/EC**

European Community: 	<b>HNH Base Gel:</b> <ul style="list-style-type: none"> <li>• HAZARD SYMBOLS: <b>Xi irritant</b></li> <li>• RISK PHRASES: <b>R22: Harmful if swallowed, R36/38: Irritating to eyes and skin R43: May cause sensitization by skin contact.</b></li> <li>• SAFETY PHRASES: <b>S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, S38: in case of insufficient ventilation, wear suitable respiratory equipment.</b></li> </ul>
------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Section 16: Other Information**

**EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):**

**Hazard Symbols:**

Xi - Irritants

**Risk Phrases:**


R36/37/38 Irritating to eyes, respiratory system and skin; R36/38 Irritating to eyes and skin; R43 May cause sensitization by skin contact

**Safety Phrases:**

S2 Keep out of reach of children; S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S27 Take off immediately all contaminated clothing; S28 After contact with skin, wash immediately with plenty of water; S29 Do not empty into drains; S30 Never add water to this product; S33 Take precautionary measures against static discharges; S35 This material and its container must be disposed of in a safe way; S36 Wear suitable protective clothing; S36/37 Wear suitable protective clothing and gloves S62 If swallowed, do not induce vomiting; seek medical advice immediately and show the container or label.

**Hazard Rating System (Pictograms)**

**NFPA:**



**HMIS:**

HEALTH	<input type="checkbox"/>
FLAMMABILITY	<input type="checkbox"/>
REACTIVITY	<input type="checkbox"/>
PERSONAL PROTECTION	<input type="checkbox"/>

This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).

**Material Safety Data Sheet**

**pH Prep**

**Section 1: Identification of the Substance/Preparation and of the Company/Undertaking**

**Product Name:** Nail Prep - pH Prep  
**Chemical Name:** N/A  
**Family:** Cleansing Agent  
**Product Use:** Nail Prep  
**Product #: 03203**

MSDS Prepared By:  
 MSDS Initial Approval Date: 9/1/2010

**Manufacture:** Artistic Nail Design, Inc  
 14509 Best Avenue; Norwalk, CA

**Emergency Phone Number:** (800) 535-5053  
**Information Contacts:** (714) 635-5110

**Section 2: Hazardous Ingredients**

Chemical Identity	CAS #	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
				OSHA TWA/STEL	ACGIH TWA/STEL	IAR/NTP/OSHA	
Isopropyl Alcohol	67-63-0	200-661-7	Isopropyl Alcohol	400 ppm	400 ppm	Not Listed	40-50
Ethyl Acetate	141-78-6	205-500-4	Ethyl Acetate	400 ppm	400 ppm	Not Listed	30-40
Isobutyl Acetate	110-19-0	203-745-1	Isobutyl Acetate	150 ppm	150 ppm	Not Listed	10-20

N/E - None Established      N/DA - No Data Available

N/R - Not Reviewed      N/A - Not Applicable

Isopropyl Alcohol:Hazard Symbols: Xi, F

Risk Phrases: R11, R36, R67

Safety Phrases: S2, S7, S16, S24/25, S26

Ethyl Acetate:Hazard Symbol -F, Xi

Risk Phrases: R11, R36, R66, R67

Safety Phrases: S2, S16, S26, S33

Isobutyl Acetate:Hazard Symbol -F

Risk Phrases-R11, R66

Safety Phrases-S2,S16,S23,S25,S29,S33

See Section 16 for Risk and Safety Phares Key

**Section 3: Hazards Identification**

**EMERGENCY OVERVIEW**

- \* **Flammable liquid and vapor!**
- \* May cause allergic skin reaction.
- \* May cause eye irritation.
- \* Avoid prolonged or repeated breathing of gases, vapors or mists.

**Potential Health Effects, Signs & Symptoms of Exposure:**

**Primary Route of Entry:** Inhalation, skin contact, eye contact

**Eye:** Vapors are irritating to the eyes. Splashes may cause severe irritation, with stinging, tearing, redness, and pain with possible corneal damage.

**Skin:** Repeated/prolonged contact may cause drying of the skin. Symptoms include redness, burning, drying, cracking and skin burn.

**Ingestion:** Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.

**Inhalation:** Vapor and mist are irritating to mucous membranes. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.

**Sub-Chronic Effects:** Significant exposure to this chemical may adversely affect people with chronic disease or may cause damage to the respiratory system, skin and eyes.

NOTE: Refer to Section 11, Toxicological Information for Details

**Section 4: First Aid Measures**

**First Aid for Eye:** Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.

**First Aid for Skin:** Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists.

**First Aid for Inhalation:** Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.

**First Aid for Ingestion:** If an individual is drowsy or unconscious do not give anything by mouth; place individual on the left side with the head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**Section 5: Fire Fighting Measures**

Flash Point	Flammable Limit	Auto-Ignition Temperature
(F/C)	(vol%)	(vol%)
TAG Closed: 68 degrees F/20 degrees C	LEL: 2%; uel:11.4%	N/DA

**Extinguishing Media:** Use CO2, dry chemical for small fires, or alcohol type aqueous film forming foam.

**Fire Fighting Instructions:** If potential for exposure to vapors or products of combustion, wear complete personal protective equipment including self contained breathing apparatus, with full face operated in pressure demand. Fight fire from a safe distance/protected location.

Flammable. When exposed to heat and flame material is a fire explosion hazard. Vapor is heavier than air and can travel considerable to source of ignition and flash back. Material creates a special hazard if it floats water.

Unusual Hazards:

---

**Section 6: Accidental Release Measures**

Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (eg. vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush or sewer. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

Spill or Release Procedures:

**Section 7: Handling and Storage**

Closed containers exposed to temperature above (120°F) in transit or storage may develop vapor pressure. Open containers slowly. Ground all metals containers when transferring material. Wash face and hands thoroughly with soap and water after handling and before eating, drinking or smoking.

Handling

Storage Store in a cool, well ventilated area away from heat, sparks and flame. Keep containers closed when not in use.

Explosion Hazard

Flammable Liquid. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**Section 8: Exposure Controls/Personal Protective Equipment**

Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Engineering Controls

**Personal Protective Equipment:**

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

General

Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/Face Protection

Skin Protection Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN149.

Respiratory Protection

**Section 9: Physical and Chemical Properties**

Appearance	Odor & Odor Threshold	pH	voc (g/L)	Specific Gravity	Viscosity	% Volatile	
Clear, colorless, mobile liquid	Fruity, pungent mix odor	NA	920	(H <sub>2</sub> O =1):0.88	N/A	W/W % : 99+	
Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log po/w	Vapor Pressure	Vapor Density	Evaporation Rate	Ignition	Solubility In Water
77°C	N/DA	N/DA	73 mm Hg @ 20°C	(Air=1):3.0	(Butyl1 Acetate=1):4.5	N/A	8.70%
Flash Point (°F/°C)		Flammable Limit (vol%)		Auto-Ignition Temperature (vol%)			
68 °F/20 °C		LEL:2% ; UEL:11.4%		N/DA			

**Section 10: Stability and Reactivity****Stability:**

Stable

**Hazardous Decomposition Products:**

Carbon Monoxide

**Conditions to Avoid:**

Heat, flame, ignition sources, and incompatibles

**Incompatibility (Materials to Avoid):**

Oxidizing agents, i.e. hydrogen peroxide, Nitric Acid, Perchloric acid, Chlorine

**Hazardous Polymerization:**

Will not occur

**Section 11: Toxicological Information**

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - Skin	Irritation - Eye
Mouse:LD50=3600 mg/kg;	N/DA	Rat=1030 ug/m <sup>3</sup> /16w	Skin, rabbit:LD50=12800 mg/kg.	N/DA
Sensitization		Mutagenicity	Sub-chronic Toxicity	
N/DA		Rat=1030 ug/m <sup>3</sup> /16W	N/DA	



**Section 12: Ecological Information****Ecotoxicological Information:**

Acute Oral Toxicity To Fish	Acute Dermal Toxicity to Invertebrates	Acute Inhalation Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
The LC50/96-hour values for fish are over 100mg/l.	N/ DA	N/ DA	N/ DA	N/ DA

**Chemical Fate Information**

<b>Biodegradability</b>	When released into the soil, this material is expected to quickly evaporate. When released into the soil, this material may leach into groundwater. When released into the soil, this material biodegrade extent. When released to water, this material is expected to quickly evaporate. When released into water, this material is expected to have a half-life between 1 and 10 days. When released into water, this material may biodegrade to a moderate extent. this material is not expected to significantly bioaccumulate.
<b>Chemical Oxygen Demand</b>	N/ DA

**Section 13: Disposable Considerations**

Dispose of diking materials and absorbent in compliance with State, Local and Federal regulations. Residual vapors may explode on ignition, do not cut, drill or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

**Section 14: Transport Information**

<b>DOT (49 CFR 172)</b>	
Proper Shipping Name:	UN1993, flammable Liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Identification Number:	UN1993
Marine Pollutant:	NO
Special Provisions:	T8, T31
<b>Emergency Response Guidebook (ERG #):</b>	<b>128</b>
<b>IATA (DGR):</b>	
Proper Shipping Name:	UN1993, flammable Liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Class or Division:	3
UN or ID Number:	UN1993
Packaging Instructions:	
<b>Emergency Response Guidebook (ICAO #):</b>	
<b>IMO (IMDG):</b>	
Proper Shipping Name:	UN1993, flammable Liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation:	None
<b>Emergency Schedule (EmS) #:</b>	
<b>Other Information:</b>	<b>Flash Point = 20°C</b>

**Section 15: Regulatory Information****US Federal Regulations**

Clean Air Act: HAP/ODS	This product contains the following (HAPS): or ODS: <b>NONE</b>
Clean Water Act: Priority Pollutant/Hazardous Substance	The following ingredients are listed as hazardous pollutants under the CWA: Isobutyl Acetate, Cas# 110-19-0. None of the ingredients are listed as primary pollutants nor are they listed as toxic pollutants.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. Its hazards are: Immediate (acute) health hazard & Fire Hazard.
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): Ethyl Acetate CAS# 141-78-6, RCRA code: U112 Characteristic of Ignitability: RCRA Code: D001
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA Title III: Section 304	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): Ethyl Acetate, CAS# 141-78-6, RQ (Lbs): 5000 Isobutyl Acetate CAS# 110-19-0, RQ (LBS) 5000.
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: Immediate (acute) health hazard & Fire Hazard.
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting requirements of Section 313 Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <b>NONE</b>


TSCA Section 8(b): Inventory  
TSCA Significant New Use Rule:

This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.

### State Regulations

CA Right-to Know- Law: California No Significant risk Rule:	Ethyle Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0. NONE
MA Right-to-Know Law:	Ethyle Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
NJ Right-to-Know Law:	Ethyle Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
PA Right-to-Know Law:	Ethyle Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
FL Right-to-Know Law:	Ethyle Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
MN Right-to-Know Law:	Ethyle Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.

### International Regulations


CDSL: Canadian Inventory (on Canadian Transitional List)	Ethyle Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0. NONE
EINECS: European Community:	Hazard Symbols: <b>Xi</b> : irritant, <b>F</b> : Highly Flammable
	Risk Phrases: <b>R11</b> : Flammable, <b>R20/22</b> : Harmful by inhalation, <b>R36/38</b> : Irritating to eyes and skin
	Safety Phrases: <b>S7/9</b> : Handle and open container with care, <b>S24/25</b> : avoid contact with skin and eyes, <b>S33</b> : take precautionary measures against static discharges, <b>S37/39</b> : wear suitable protective clothing and gloves and eye/face protection, <b>S45</b> : in case of accident or if you feel unwell, seek medical advice immediately and (show this container or label.)

### Section 16: Other Information

#### EU Classes and Risk / Safety Phrases for Referenced ingredients ( See Section 2):

F-Flammable substance or preparations
Xi-Irritants
<b>Risks Phrases:</b> R11- Highly flammable; R36-Irritating to eyes: R66-Repeated exposure may cause skin dryness or cracking: R67- Vapors may cause drowsiness and dizziness
<b>Safety Phrases:</b> S2 Keep out of reach of children: S7 Keep container tightly closed: S16 Keep away from sources of ignition-No Smoking: S23 Do not breath gas/fumes/vapor/spray S24/25 Avoid contact with skin and eyes: S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice S29 Do not empty into drains: S33 Take precautionary measures static discharges

NFPA:




HEALTH

FLAMMABILITY

REACTIVITY

HMIS:



Revised Sections Since Last Verion:	NONE
-------------------------------------	------

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Systems at 1(800) 535-5053.

Material Safety Data Sheet

Artistic Colour Gloss Base Gel

**Section 1: Identification of the Substance/Preparation and of the Company/Undertaking**

**Product Name:** Artistic Colour Gloss Base Gel  
**Chemical Name:** N/A

MSDS Prepared By:  
 MSDS Initial Approval Date: 9/1/2010

**Family:** Soak Off Gel

**Manufacture:** Artistic Nail Design, Inc  
 14509 Best Ave unit B Norwalk, Ca 90650

**Product Use:**  
**Product #: 03200**

**Emergency Phone Number:** (800) 535-5053  
**Information Contacts:** (562) 623-4203

**Section 2: Hazards Identification**

**EMERGENCY OVERVIEW**

This information is based on findings from related or similar materials.

- May be slightly toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause eye irritation

**Potential Health Effects, Signs and Symptoms of Exposure:**

Primary Route of Entry: No specific information available. Although, this product opposes only slight irritation concern with all routes of entry.  
 Eye: No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation  
 Skin: No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.  
 Ingestion: No specific information available. Contains materials that may be practically nontoxic.  
 Inhalation: No specific information available. Low volatility makes vapor inhalation unlikely.  
 Sub-Chronic Effects: No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section II, Toxicological Information for Details

**Section 3: Composition/Information on Ingredients**

Chemical Identity	CAS#	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	Not Listed	60-70
2-Hydroxyethyl Methacrylate	868-77-9	212-782-2	HEMA	N/E	N/E	Not Listed	5-10
Hydroxypropyl Methacrylate	27813-02-1	248-666-3	Hydroxypropyl methacrylate	N/E	N/E	Not Listed	5-10
Isobornyl Methacrylate	7534-94-3	231-403-1	Isobornyl Methacrylate	N/E	N/E	Not Listed	5-10
Acrylic Acid	79-10-7	201-177-9	N/E	N/E	2 ppm	3/no/no	0-1
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
N/E - None Established	N/DA - No Data Available		* See section 16				
N/R - Not Reviewed	N/A - Not Applicable						

Polyurethane Acrylate Oligomer:	Hazard Symbol: Xi	Risk Phrases: R36/37/38	Safety Phrases: S14, S3/7, S62
2-Hydroxy ethyl methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36/38, R43	Safety Phrases: S2, S26, S28
Hydroxypropyl Methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36//37/38, R43	Safety Phrases: S6, S26, S28
Isobomyl Methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36/37/38	Safety Phrases: S26,S27,S28,S29,S30,S33,S35,S36

See Section 16 for Risk and Safety Phrase Key

**Section 4: First Aid Measures**

First Aid for Eye: Flush with plenty of water for 15 minutes and seek medical attention immediately.  
 First Aid for Skin: Remove contaminated clothing and wash contact area with soap and water for 15 minutes.  
 First Aid for Inhalation: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.  
 First Aid for Ingestion: If appreciable quantities are swallowed, seek medical attention.

**Section 5: Fire Fighting Measures**

Flash Point ( °F/ °C)	Flammable Limit (Vol%)	Auto-ignition Temperature (vol%)
-----------------------	------------------------	----------------------------------

>212 °F/100 °C Seta flash	No Data	No Data
---------------------------	---------	---------

<b>Method:</b>	
Extinguishing Media:	Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.
Unusual Hazards:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

### Section 6: Accidental Release Measures

Spill or Release Producers:	Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detergent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.
-----------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Section 7: Handling and Storage

Handling:	Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheating of product, this will also diminishing the quality of the product.
Storage:	Product is extremely light sensitive. If exposed to natural light, LED, UVA, UVB or UV any light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.
Explosion Hazard:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

### Section 8: Exposure Controls / Personal Protection

Engineering Controls	Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.
<b>Personal Protective Equipment</b>	
General:	To identify additional Personal protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron boots, or whole body suits. Nitrile rubber is better than PVC.
Eye / Face Protection:	Wear chemical splash goggles
Skin Protection:	Wear impervious gloves (Neoprene)
Respiratory Protection:	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

### Section 9: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	%Volatile
Clear to slight violet, viscous liquid	characteristic acrylate odor	NA	(H2O=1): 1.15	N/DA	By Volume: <0.5

Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure: (mm Hg) @ 20 C:<0.01	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A		No Data	No Data	No Data	Insoluble

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
>212 °F/100 °C Seta flash	No Data	No Data

### Section 10: Stability and Reactivity

Stability	<b>Incapability (Material to Avoid):</b>
Normally Stable	Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.

**Hazardous Decomposition Products:**

Fumes produced when heated to decomposition may include:

carbon monoxide, carbon dioxide

**Conditions to Avoid:**

Storage <100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization, contamination with incompatible materials.

**Hazardous Polymerization:**

May occur --- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

**Section 11: Toxicological Information**

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No info available	No info available	No info available	No info available	No info available
Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.				
Sensitization	Mutagenicity	Sub-chronic Toxicity		
N/DA	N/DA	N/DA		

**Section 12: Ecological Information****Ecotoxicological Information**

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

**Chemical Fate Information**

<b>Biodegradability</b>	N/DA
<b>Chemical Oxygen Demand</b>	N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil.

**Section 13: Disposal Considerations**

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste.

Comply with all federal, state, and local regulations. Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

**Section 14: Transport Information****DOT (49 CFR 172)**

Proper Shipping Name: Non-Regulated Material  
 Identification Number: N/A  
 Marine Pollutant: No  
 Special Provisions: N/A

**Emergency Response Guidebook (ERG) #:**

**N/A**

**IATA (DGR):**

Proper Shipping Name: Non-Regulated Material  
 Class or Division: N/A  
 UN or ID Number: N/A  
 Packaging Instructions:

**Emergency Response Guidance (ICAO)#:****IMO (IMDG):**

Proper Shipping Name: Non-Regulated Material  
 Class or Division: N/A  
 UN or ID Number: N/A  
 Special Provisions & Stowage/Segregation: None

**Emergency Schedule (EmS)#:**

**Other Information: Flash point >100 °C**

**Section 15: Regulatory Information****US Federal Regulations**

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: <ul style="list-style-type: none"> <li>Acrylic Acid CAS# 79-10-7(HAP)</li> </ul> This product contains no ODS's
Clean Water Act: Priority Pollutant	This product contains no chemicals listed under the U.S. Clean Water Act Priority Pollutant List
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazard are: <ul style="list-style-type: none"> <li>Immediate (acute) health hazard</li> <li>Delayed (chronic) health hazard</li> <li>Reactive hazard</li> </ul>
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261)
SARA Title III: Section 302 (TPQ)	This product contains the following chemicals regulated under Sec. 302 as extremely hazardous substance that carry a TPQ. <ul style="list-style-type: none"> <li>NONE</li> </ul>
SARA Title III: Section 304	This product contains the following chemicals regulated under Section 304 as extremely hazardous chemical for

	<p>emergency release notification ("CERCLA" List):</p> <ul style="list-style-type: none"> <li>● Acrylic Acid CAS #79-10-7 RG (LBS) 5000</li> </ul>
SARA Title III: Section 311-312:	<p>This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are:</p> <ul style="list-style-type: none"> <li>● Immediate (acute) health hazard</li> <li>● Delayed (chronic) health hazard</li> <li>● Reactive hazard</li> </ul>
SARA Title III: Section 313:	<p>This product contains the following chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:</p> <p>Acrylic Acid CAS #79-10-7</p>
TSCA Section 8(b) Inventory:	<p>This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.</p>
TSCA Significant New Use Rule:	<p>None of the chemicals listed have a SNUR under TSCA.</p>


#### State Regulations

CA Right-to-Know Law:	Acrylic Acid CAS #79-10-7
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Acrylic Acid CAS #79-10-7
NJ Right-to-Know Law:	Acrylic Acid CAS #79-10-7
PA Right-to-Know Law:	Acrylic Acid CAS #79-10-7
FL Right-to-Know Law:	Acrylic Acid CAS #79-10-7
MN Right-to-Know Law:	NONE

#### International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	<p>Hydroxypropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B</p> <p>Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS - n/da</p> <p>2-Hydroxyethyl methacrylate CASE# 868-77-9 is on the DSL List. WHMIS - n/da</p> <p>Isobornyl Methacrylate CAS# 7534-94-3 is on the DSL list. WHMIS - n/da</p> <p>Acrylic Acid CAS #79-10-7 is on the DSL list. WHMIS - B2, E, DIA, F</p>
----------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### Labeling according to EC Directives - 1999/45/EC

<p>European Community:</p> 	<p><b>HNH Base Gel:</b></p> <ul style="list-style-type: none"> <li>● HAZARD SYMBOLS: <b>Xi irritant</b></li> <li>● RISK PHRASES: <b>R22: Harmful if swallowed, R36/38: Irritating to eyes and skin R43: May cause sensitization by skin contact.</b></li> <li>● SAFETY PHRASES: <b>S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, S38: in case of insufficient ventilation, wear suitable respiratory equipment.</b></li> </ul>
----------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### Section 16: Other Information

##### EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

###### Hazard Symbols:

Xi - Irritants



###### Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin; R43 May cause sensitization by skin contact

###### Safety Phrases:

S2 Keep out of reach of children; S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S27 Take off immediately all contaminated clothing; S28 After contact with skin, wash immediately with plenty of water; S29 Do not empty into drains; S30 Never add water to this product; S33 Take precautionary measures against static discharges; S35 This material and its container must be disposed of in a safe way; S36 Wear suitable protective clothing; S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label; 36/37 Wear suitable protective clothing and gloves; S62 If swallowed, do not induce vomiting; seek medical advice immediately and show the container or label.

#### Hazard Rating System (Pictograms)

<p><b>NFPA:</b></p> 	<p><b>HMIS:</b></p> 
----------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------

disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).

---



## Material Safety Data Sheet

## Artistic Colour Gloss - Gel Remover

## Section 1: Identification

**Product Name:** Artistic Colour Gloss - Gel Remover**Chemical Name:** N/A

MSDS Prepared By:

MSDS Initial Approval Date:

September 2010

**Family:** Remover**Manufacture:**

Artistic Nail Design, Inc

14509 Best Ave unit B Norwalk, Ca 90650

**Product Use:** Soak Off Gel Polish**Emergency Phone Number:** (800) 535-5053**Product #:** 03206 & 03207**Information Contacts:** (714) 635-5110

## Section 2: Information on Ingredients

Chemical Identity	CAS#	EINECS#	INCI Name	Exposure OSHA	Limits ACGIH TWA/STEL	Carcinogen	%
Acetone	67-64-1	200-662-2	Acetone	750ppm /1000ppm	500ppm / 750ppm	N/A	90
DI Water	N/A	N/A	N/A	N/A	N/A	N/A	10
Propylene Glycol	57-55-6	200-338-0	Propylene Glycol	N/A	N/A	N/A	<0.1%
Vitamin E	10191-41-0	200-412-2	Tocopherol	N/A	N/A	N/A	<0.1%
Red #33	3567-66-6	222-656-9	Acid Red 33	N/A	N/A	N/A	<0.1%
Rose Fragrance							
3, 7-Dimethyl -7-							
Hydroxyoctanal, 98%	107-75-5	203-518-7	Hydroxycitronellal	N/A	N/A	N/A	<0.1%
2-Phenethyl Alcohol	60-12-8	200-456-2	Phenethyl Alcohol	N/A	N/A	N/A	<0.1%
Geranyl Acetate	105-87-3	203-341-5	Geranyl Acetate	N/A	N/A	N/A	<0.1%
Geraniol	106-24-1	203-377-1	Geraniol	N/A	N/A	N/A	<0.1%
Dipropylene Glycol	25265-71-8	246-770-3	Dipropylene Glycol	N/A	N/A	N/A	<0.1%
Palmarosa Oil	8014-19-5	283-461-2	Cymbopogon Martini	N/A	N/A	N/A	<0.1%
Benzyl Acetate	140-11-4	205-399-7	Benzyl Acetate	N/A	10ppm TWA	N/A	<0.1%
Alpha-Amyl Cinnamic Aldehyde	122-4-7	204-541-5	Amyl Cinnamal	N/A	N/A	N/A	<0.1%
a-(trichloromethyl) Benzyl Acetate	90-17-5	201-972-0	Trichloromethyl Phenyl Carbonyl Acetate	N/A	N/A	N/A	<0.1%
Tetrahydro-4-methyl-2-(2-methylprop-1-enyl)pyran	16409-43-1	240-457-5	Isobutenyl Methyltetrahydropyran	N/A	N/A	N/A	<0.1%
Citronellol	106-22-9	203-375-0	Citronellol	N/A	N/A	N/A	<0.1%

## Section 3: Fire and Explosion Hazard Data

**Flash Point:**

(Closed Cup F)

**Extinguishing Media:**[ ] water [x] CO<sub>2</sub> [ ] Dry Chemical [x] Foam [ ] water fog**Special Fire Fighting Procedure:**

Firefighters to cool fire-exposed containers, use blanketing effect. Use self contained breathing apparatus

**Unusual Fire & Explosion Hazards:**

Dangerous fire hazard and moderate explosion hazard when exposed to heat and flame

**NFPA Flammability Code:**

2

## Section 4: Reactivity Data

**Stability:**

Presents no significant reactivity hazard, not pyrophoric nor reactive with water.

**Incompatibility:****Materials to avoid:**

Avoid strong oxidizers

**Hazardous Combustion or Decomposition:**Burning liberates CO, CO<sub>2</sub> and smoke. Does not form explosive mixtures with organic materials. Does not undergo explosive decomposition and is shock stable. It is not an oxygen donor.**Hazardous Polymerization:**

Will not undergo spontaneous exothermic polymerization.

**NFPA Reactivity Code:**

0

## Section 5: Spill or Leakage Procedures

**Clean-up & Spills:**

Clean-up of spills or accidental release of material, flush with water or soak up with suitable absorbent. Incineration or sanitary landfill in accordance with local, state and federal

**Waste Disposal Methods:**

regulations and consistent with good ecological practices.

## Section 6: Special Protection Information

**Respiratory:** Use NIOSH / MSHA approved respirator if TLV is exceeded  
**Ventilation:** General mechanical  
**Protective Gloves:** Volatile resistant if skin contact is anticipated  
**Eye Protection:** Splash proof goggles if handling methods warrant them.

### Section 7: Emergency and First Aid Procedures

**Eye:** In the event of accidental contact with eyes, irrigate copious amounts of water, if irritation persists obtain medical advise.  
**Skin:** Remove contained clothing. Flush exposed areas with copious amounts mild soap and water. Material may remove some of the natural oils in the skin. If irritation persists obtain medical advise.  
**Ingestion:** In the event of accidental ingestion rinse the mouth with water. Give up to one tumbler (half pint) of milk or water. Obtain medical advise immediately.

### Section 8: Exposure Data

**Primary Route of Exposure:** Skin contact & possible inhalation.  
 The approximate vapor pressure of the mixture is sufficiently high enough to be a significant route of exposure.  
**OSHA PEL:** Not Determined  
**ACGIH TLV:** Not Determined  
 material is not found on any know list of carcinogen such as NTP, IARC or by OSHA nor does it contain any carcinogens found in these lists.

### Section 9: Health Hazards

The identity of the individual components of this mixture is proprietary information and is regarded to be a trade secret. In accordance with 29 CFR 1910.1200 we have to assume that the mixture presents the same health hazards as the individual components when they are present at greater than 10% concentration.

Listed below are the health hazards for all the material present of 10% concentration and that undiluted have health hazards associated with them. Note that all the components of the mixture have health hazards associated with them. In the event of a medical emergency the identity of all the components will be divulged to a qualified health professional.

The following effects are concluded as a result of laboratory testing on one or more of the individual components. The relevancy to the mixture or to humans is unknown. Excessive exposure may cause similar effects.

Repeated daily doses orally and dismally caused damage to the nervous system.

Toxic prolonged skin contact may cause serious health effects.  
 Repeated daily oral dosing of large amounts caused liver damage  
 Repeated daily oral dosing of large amounts caused kidney damage  
 Skin contact at full strength may cause irritation and also be an eye irritant  
 Repeated oral dosing increased ocular tension  
 repeated daily application to skin caused reproductive effects

The following effects were concluded as a result of human testing and observation of one or more of the individual components.

Liquid and vapor may is irritating to the skin and eyes.  
 Vapor is irritating to the throat and lungs.  
 Breathing high concentration of vapor may cause anesthetic effects.  
 Will cause dermatitis after long term skin contact in sunlight.  
 Repeated contact may cause allergic dermatitis.  
 Liquid is irritating to skin and corrosive to eyes.

### Section 10: Stability and Reactivity

<b>Stability:</b> Stable	<b>Incompatibility (Materials to Avoid):</b> Oxidizing agents, i.e. hydrogen peroxide, Nitric Acid, Perchloric Acid, Perchloric Acid, Chromium Trioxide
<b>Hazardous Decomposition Products:</b> Carbon Monoxide	<b>Hazardous Polymerization:</b> Will not occur
<b>Conditions to Avoid:</b> Heat, flames, ignition sources, and incompatibles	

### Section 11: Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - Skin	Irritation - Eye
Mouse: LD50 = 3600 mg/kg;	N/DA	Rat=1030 ug/m3/16W	Skin, rabbit:LD50=12800 mg/kg.	N/DA
Sensitization	Mutagenicity		Sub-chronic Toxicity	
N/DA	Rat=1030 ug/m3/16W		N/DA	

### Section 12: Ecological Information

Ecotoxicological Information:

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria

The LC50/96-hour values for fish are over 100mg/l.	N/ DA	N/ DA	N/ DA	N/ DA
----------------------------------------------------	-------	-------	-------	-------

#### Chemical Fate Information

<b>Biodegradability</b>	When released into the soil, this material is expected to quickly evaporate. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade extent. When released to water, this material is expected to quickly evaporate. When released into water, this material is expected to have a half-life between 1 and 10 days. When released into water, this material may biodegrade to a moderate extent. This material is not expected to significantly bioaccumulate.
-------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>Chemical Oxygen Demand</b>	N/ DA
-------------------------------	-------

#### Section 13: Disposable Considerations

Dispose of diking materials and absorbent in compliance with State, Local and Federal regulations. Residual vapors may explode on ignition, do not cut, drill or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

#### Section 14: Transport Information

<b>DOT (49 CFR 172)</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Identification Number:	UN1993
Marine Pollutant:	No
Special Provisions:	T8, T31
<b>Emergency Response Guidebook (ERG) #:</b>	<b>128</b>
<b>IATA (DGR):</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Class or Division:	3
UN or ID Number:	UN1993
Packaging Instructions:	
<b>Emergency Response Guidebook (ICAO #):</b>	
<b>IMO (IMDG):</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation:	None
<b>Emergency Schedule (EmS) #:</b>	
<b>Other Information:</b>	<b>Flash Point = 20°C</b>

#### Section 15: Regulatory Information

##### US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following (HAP's): or ODS: • NONE
Clean Water Act: Priority Pollutant	The following ingredients are listed as hazardous pollutants under the CWA: • Isobutyl Acetate, CAS# 110-19-0 None of the ingredients are listed as primary pollutants nor are they listed as toxic pollutants.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging an indirect food-packaging additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication hazards are: • Immediate (acute) • Fire hazard
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): • Ethyl Acetate CAS# 141-78-6, RCRA Code: U112 • Characteristic of Ignitability, RCRA Code: D001
SARA Title III: Section 302	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA title III: Section 304	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): • Ethyl Acetate CAS# 141-78-6, RQ (Lbs) 5000

	<ul style="list-style-type: none"> <li>Isobutyl Acetate, CAS# 110-19-0, RQ (Lbs) 5000</li> </ul>
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> <li>Immediate (acute) health hazard</li> <li>Fire hazard</li> </ul>
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting requirements of Section 313 Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <ul style="list-style-type: none"> <li>Isopropyl Alcohol CAS#</li> </ul>
TSCA Section 8(b): Inventory	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.



#### State Regulations

CA Right-to-Know- Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
NJ Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
PA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
FL Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
MN Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.

#### International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
-------------------------------------------------------------	----------------------------------------------------------------------------------------------

#### Labeling according to EC Directives - 1999/45/EC

European Community:   	<b>B-2 Nail Prep Primer:</b> <ul style="list-style-type: none"> <li>HAZARD SYMBOLS: <b>Xn, F:</b> harmful, <i>Highly Flammable</i></li> <li>RISK PHRASES: <b>R11:</b> <i>highly flammable</i>, <b>R20/22:</b> <i>Harmful by inhalation and if swallowed</i>, <b>R36/37/38:</b> <i>Irritating to eyes, respiratory system and skin</i></li> <li>SAFETY PHRASES: <b>S7/9:</b> <i>keep container tightly closed and in a well ventilated place</i>, <b>S16:</b> <i>keep away from sources of ignition-no smoking</i>, <b>S24/25:</b> <i>avoid contact with skin and eyes</i>, <b>S33:</b> <i>take precautionary measures against static discharges</i>, <b>S37/39:</b> <i>wear suitable gloves and eye/face protection</i>, <b>S45:</b> <i>In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible)</i></li> </ul>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### Section 16: Other Information

##### EU Classes and Risk / Safety Phrases for Referenced ingredients ( See Section 2):

F-Flammable substance or preparations

Xi-Irritants

##### Risks Phrases:


R11- Highly flammable; R36-Irritating to eyes; R66-Repeated exposure may cause skin dryness or cracking; R67- Vapors may cause drowsiness and dizziness

##### Safety Phrases:

S2 Keep out of reach of children; S7 Keep container tightly closed; S16 Keep away from sources of ignition-No Smoking;  
 S23 Do not breathe gas/fumes/vapor/spray S24/25 Avoid contact with skin and eyes; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice  
 S29 Do not empty into drains; S33 Take precautionary measures against static discharges

#### Hazard Rating System (Pictograms)

NFPA:



Revised Sections Since Last Verion:	NONE
-------------------------------------	------

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Systems at 1(800) 535-5053.











Material Safety Data Sheet

Artistic Colour Gloss Top Gel

**Section 1: Identification of the Substance/Preparation and of the Company/Undertaking**

**Product Name:** Artistic Colour Gloss Top Gel  
**Chemical Name:** N/A

MSDS Prepared By:  
 MSDS Initial Approval Date: 9/1/2010

**Family:** Soak Off Gel

**Manufacture:** Artistic Nail Design, Inc  
 14509 Best Ave unit B Norwalk, Ca 90650

**Product Use:**  
**Product #: 03201**

**Emergency Phone Number:** (800) 535-5053  
**Information Contacts:** (562) 623-4203

**Section 2: Hazards Identification**

**EMERGENCY OVERVIEW**

This information is based on findings from related or similar materials.



- Flammable liquid and vapor!
- May be slightly toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause chemical burn in eye

**Potential Health Effects, Signs and Symptoms of Exposure:**

Primary Route of Entry: No specific information available.  
 Eye: Contains materials that are essentially nonirritating, but contact may cause slight transient irritation. Material may act as a Lachrymator (a substance which increases the flow of tears).  
 Skin: Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.  
 Ingestion: May cause gastrointestinal irritation with nausea, vomiting and diarrhea.  
 Inhalation: May cause respiratory tract irritation with presence of monomer. Vapors may cause dizziness or suffocation.  
 Sub-Chronic Effects: No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section II, Toxicological Information for Details

**Section 3: Composition/Information on Ingredients**

Chemical Identity	CAS#	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	Not Listed	70-75
2-Hydroxyethyl Methacrylate	109-17-1	203-653-1	PEG-4 Dimethacrylate	N/E	N/E	Not Listed	15-20
Ethyl Methacrylate	97-63-2	202-597-5	Ethyl Methacrylate	100 ppm	100 ppm	Not Listed	5-10
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	1-3
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
N/E - None Established	N/DA - No Data Available		* See section 16				
N/R - Not Reviewed	N/A - Not Applicable						

Polyurethane Acrylate Oligomer:	Hazard Symbol: Xi	Risk Phrases: R36/37/38	Safety Phrases: S14, S3/7, S62
2-Hydroxy ethyl methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36/38, R43	Safety Phrases: S21, S24/25, S26, S41
Hydroxypropyl Methacrylate:	Hazard Symbol: Xi	Risk Phrases: R11, R36//37/38, R43	Safety Phrases: S2, S9, S16, S29, S33
Isobomyl Methacrylate:	Hazard Symbol: Xi	Risk Phrases: R36, R37, R38	Safety Phrases: S26, S37

See Section 16 for Risk and Safety Phrase Key

**Section 4: First Aid Measures**

First Aid for Eye: Flush with plenty of water for 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid. Do NOT allow victim to rub or keep eyes closed.

First Aid for Skin: Remove contaminated clothing and wash contact area with soap and water for 15 minutes. Get medical aid if symptoms persist. Wash clothing before reuse.

First Aid for Inhalation: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.

First Aid for Ingestion: Never give anything by mouth to an unconscious person. Get medical aid. Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2 to 4 cupfuls of milk or water.

**Section 5: Fire Fighting Measures**

Flash Point ( °F/ °C)	Flammable Limit (Vol%)	Auto-ignition Temperature (vol%)
-----------------------	------------------------	----------------------------------

110°F/43°C Penske-Martin	No Data	No Data
--------------------------	---------	---------

<b>Method:</b>	
Extinguishing Media:	Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.
Unusual Hazards:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

### Section 6: Accidental Release Measures

Spill or Release Producers:	Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e.g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.
-----------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Section 7: Handling and Storage

Handling:	Ground and bond containers when transferring material. Avoid contact with skin and eyes, and clothing. Use with adequate ventilation and avoid breathing in vapor. Keep container closed when not in use. Avoid contact with heat, sparks and flame. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks, or open flames. <b>Material is extremely light sensitive.</b> Use extreme care and do not expose to natural or UV light, unless using material for it's intended use. Since the material is very photosensitive any type of light may initiate the curing process.
Storage:	Product is extremely light sensitive. If exposed to natural light, LED, UVA, UVB or UV any light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.
Explosion Hazard:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

### Section 8: Exposure Controls / Personal Protection

Engineering Controls	Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.
<b>Personal Protective Equipment</b>	
General:	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard En166 be conducted before using this product. Provide eye stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye / Face Protection:	Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye and face contact due to splashing or spraying material.
Skin Protection:	Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Respiratory Protection:	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN149.

### Section 9: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	%Volatile
Clear, semi-viscous liquid	characteristic acrylate odor	NA	(H2O=1): 1.14	N/DA	By Volume: <0.5

Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure: (mm Hg) @ 20 C:<0.01	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A		No Data	No Data	No Data	Insoluble

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
110°F/43°C Penske-Martin	No Data	No Data

### Section 10: Stability and Reactivity

<b>Stability</b>	<b>Incapability (Material to Avoid):</b>
Normally Stable	Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust

and strong bases.

**Hazardous Decomposition Products:**

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide

**Hazardous Polymerization:**

May occur --- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

**Conditions to Avoid:**

Storage<100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization, contamination with incompatible materials.

**Section 11: Toxicological Information**

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No info available	No info available	No info available	No info available	No info available
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.				
Sensitization	Mutagenicity	Sub-chronic Toxicity		
No Information Available	No Information Available	No Information Available		

**Section 12: Ecological Information**

**Ecotoxicological Information**

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No Information Available	No Information Available	No Information Available	No Information Available	No Information Available

**Chemical Fate Information**

<b>Biodegradability</b>	No Information Available
<b>Chemical Oxygen Demand</b>	No Information Available

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

**Section 13: Disposal Considerations**

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member State, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

**Section 14: Transport Information**

**DOT (49 CFR 172)**

Proper Shipping Name: UN1993, Flammable liquids, n.o.s., (ethyl methacrylate, acrylic esters), 3, PGIII  
 Identification Number: UN1993  
 Marine Pollutant: No  
 Special Provisions: N/A  
**Emergency Response Guidebook (ERG) #:** 128

**IATA (DGR):**

Proper Shipping Name: UN1993, Flammable liquids, n.o.s., (ethyl methacrylate, acrylic esters), 3, PGIII  
 Class or Division: 3.2  
 UN or ID Number: UN1993  
 Packaging Instructions:

**Emergency Response Guidance (ICAO)#:**

**IMO (IMDG):**

Proper Shipping Name: UN1993, Flammable liquids, n.o.s., (ethyl methacrylate, acrylic esters), 3, PGIII  
 Class or Division: 3  
 UN or ID Number: Un1993  
 Special Provisions & Stowage/Segregation: None

**Emergency Schedule (EmS)#:**

**Other Information:** Flash point >43°C

**Section 15: Regulatory Information**

**US Federal Regulations**

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: <ul style="list-style-type: none"> <li>NONE</li> </ul> This product does not contain any Class I or Class 2 ODS
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA: <ul style="list-style-type: none"> <li>NONE</li> </ul> This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> <li>Immediate (acute) health hazard</li> <li>Delayed (chronic) health hazard</li> <li>Reactive hazard</li> </ul>

RCRA	This product is considered to be a hazardous waste under RCRA (40 CFR 261) RCRA Code: <ul style="list-style-type: none"> <li>Ethyl methacrylate, CAS# 97-63-2, RCRA Code: U1118</li> <li>Characteristic of Ignitability, RCRA Code: D001</li> </ul>
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): <ul style="list-style-type: none"> <li>Ethyl methacrylate, CAS# 97-63-2, RQ (Lbs): 1000</li> </ul>
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> <li>Immediate (acute) health hazard</li> <li>Delayed (chronic) health hazard</li> <li>Reactive hazard</li> </ul>
SARA Title III: Section 313:	This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <ul style="list-style-type: none"> <li>NONE</li> </ul>
TSCA Section 8(b) Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals in this material have a SNUR under TSCA.



### State Regulations

CA Right-to-Know Law:	NONE
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
NJ Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
PA Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
FL Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
MN Right-to-Know Law:	NONE

### International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Ethyl methacrylate CAS #97-63-2 is on the DSL List. WHMIS = B2, D2B. Tetraethylene glycol dimethacrylate, CAS # 109-17-1 is not on the DSL List. WHMIS = n/da Hydroxycyclohexyl phenyl ketone CAS #947-19-3 is on the DSL List. WHMIS = n/da D&C Violet #2, CAS # 81-48-1 is not on the DSL List. WHMIS = n/da
-------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



### Labeling according to EC Directives - 1999/45/EC

European Community:	 
	<b>HNH Base Gel:</b> <ul style="list-style-type: none"> <li>HAZARD SYMBOLS: <b>Xi irritant</b>, <b>F: Flammable</b></li> <li>RISK PHRASES: <b>R22: Harmful if swallowed</b>, <b>R36/38: Irritating to eyes, respiratory system, and skin</b>, <b>R43: May cause sensitization by skin contact</b>.</li> <li>SAFETY PHRASES: <b>S18: Handle and open container with care</b>, <b>S24/25: avoid contact with skin and eyes</b>, <b>S36/37: Wear suitable protective clothing and gloves</b>, <b>S38: in case of insufficient ventilation, wear suitable respiratory equipment</b>, <b>S46: If swallowed seek medical advise immediatley and show this container or label</b>.</li> </ul>

### Section 16: Other Information

<b>EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):</b>	
<b>Hazard Symbols:</b>	
Xi - Irritants	
F - Flammable substances or preparations	
<b>Risk Phrases:</b>	
R11 Highly flammable; R36/37/38 Irritating to eyes, respiratory system and skin; R43 May cause sensitization by skin contact	
<b>Safety Phrases:</b>	
S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; S9 Keep container in a well-ventilated place; S16 Keep away from sources of ignition - No smoking; S21 When using do not smoke; S24/25 Avoid contact with skin and eyes; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S29 Do not empty into drains; S33 Take precautionary measures against static discharges; S37 Wear suitable gloves; S41 In case of fire and/or explosion do not breathe fumes; S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.	

### Hazard Rating System (Pictograms)

NFPA:		HMIS:	
-------	--------------------------------------------------------------------------------------	-------	---------------------------------------------------------------------------------------

---

This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).

---

## Material Safety Data Sheet

## Artistic Colour Gloss - Gel Cleanser

### Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

<b>Product Name:</b>	Artistic Colour Gloss - Gel Cleanser	<b>MSDS Prepared By:</b>	
<b>Chemical Name:</b>	N/A	<b>MSDS Initial Approval Date:</b>	9/1/2010
<b>Family:</b>	Cleansing Agent	<b>Manufacture:</b>	Artistic Nail Design, Inc 14509 Best Ave unit B Norwalk, Ca 90650
<b>Product Use:</b>	Gel Cleanser	<b>Emergency Phone Number:</b>	(800) 535-5053
<b>Product #:</b>	03204 & 03205	<b>Information Contacts:</b>	(714)635-5110

### Section 2: Hazardous Ingredients

Chemical Identity	CAS #	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IAR/NTP/OSHA	%
Isopropyl Alcohol	67-63-0	200-661-7	Isopropyl Alcohol	400 ppm	400 ppm	Not Listed	40-50
Ethyl Acetate	141-78-6	205-500-4	Ethyl Acetate	400 ppm	400 ppm	Not Listed	30-40
Isobutyl Acetate	110-19-0	203-745-1	Isobutyl Acetate	150 ppm	150 ppm	Not Listed	20-10

N/E - None Established

N/DA - No Data Available

N/R - Not Reviewed

N/A - Not Applicable

**Isopropyl Alcohol:** Hazard Symbols: Xi, F

**Risk Phrases:** R11, R36, R67

**Safety Phrases:** S2, S7, S16, S24/25, S26

**Ethyl Acetate:** Hazard Symbol - F, Xi

**Risk Phrases:** R11, R36, R66, R67

**Safety Phrases:** S2, S16, S26, S33

**Isobutyl Acetate:** Hazard Symbol - F

**Risk Phrases:** R11, R66

**Safety Phrases:** S2, S16, S23, S25, S29, S33

See Section 16 for Risk and Safety Phrases Key

### Section 3: Hazards Identification

#### EMERGENCY OVERVIEW

\* **Flammable liquid and vapor!**

\* May cause eye irritation.

\* May cause skin irritation

\* Avoid prolonged or repeated breathing of gases, vapors or mists.

\* Please read entire MSDS for additional information



#### Potential Health Effects, Signs & Symptoms of Exposure:

Primary Route of Entry	Inhalation, skin and ingestion
Eye	Vapors are irritating to the eyes. Splashes may cause severe irritation, with stinging, tearing, redness, and pain with possible corneal damage.
Skin	Repeated/prolonged contact may cause drying of the skin. Symptoms include redness, burning, drying, cracking and skin burns.
Ingestion	Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.
Inhalation	Vapor are irritating to nasal passages and throat and may cause stupor or headache. Symptoms usually occur at air concentrations higher than the recommended exposure limits.
Sub-Chronic Effects	Significant exposure to this chemical may adversely affect people with chronic disease or may cause damage to the respiratory system, skin and eyes.

NOTE: Refer to Section 11, Toxicological Information for Details

### Section 4: First Aid Measures

First Aid for Eye	Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.
First Aid for Skin	Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists.
First Aid for Ingestion	If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.
First Aid for Inhalation	Remove to fresh air. If having breathing difficulty, give oxygen. If breathing has stopped, give artificial respiration. Seek medical attention if discomfort persists.

### Section 5: Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-Ignition Temperature (vol%)
68° F/ 20° C	LEL: 2%; UEL: 11.4%	N/DA

Extinguishing Media:	Use CO2, dry chemical for small fires, or alcohol type aqueous film forming foam.
Fire Fighting Instructions:	If potential for exposure to vapors or products of combustion, wear complete personal protective equipment including self contained breathing apparatus, with full face operated in pressure demand. Fight fire from a safe distance/protected location.
Unusual Hazards:	Flammable. When exposed to heat and flame material is a fire explosion hazard. Vapor is heavier than air and can travel considerable source of ignition and flash back. Material creates a special hazard if it floats water.

### Section 6: Accidental Release Measures

Spill or Release  
Procedures:

Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (eg. vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush or sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

## Section 7: Handling and Storage

Handling	Closed containers exposed to temperature above (120°F) in transit or storage may develop vapor pressure. Open containers slowly. Ground all metals containers when transferring material. Wash face and hands thoroughly with soap and water after handling and before eating, drinking or smoking.
Storage	Store in a cool, well ventilated area away from heat, sparks and flame. Keep containers closed when not in use.
Explosion Hazard	Flammable liquid. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

## Section 8: Exposure Controls/Personal Protective Equipment

Engineering Controls Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

### Personal Protective Equipment:

General	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye/Face Protection	Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of safety glasses.
Skin Protection	Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Neoprene and Nitrile rubber is better than PVC.
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN 149.

## Section 9: Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	voc (g/L)	Specific Gravity	Viscosity	% Volatile	
Clear, colorless, mobile liquid	Fruity, pungent mix odor	N/A	920	(H2O =1):0.92	N/A	W/W % : 99+	
Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
77°C	N/DA	N/DA	73 mm Hg @ 20°C	(Air=1):3.0	(Buty1 Acetate=1); 4.5	N/A	8.70%
Flash Point (°F/C)	Flammable Limit (vol%)	Auto-Ignition Temperature (vol%)					
68 °F/20 °C	LEL:2% ; UEL:11.4%	N/DA					

## Section 10: Stability and Reactivity

<b>Stability:</b> Stable  <b>Hazardous Decomposition Products:</b> Carbon Monoxide  <b>Conditions to Avoid:</b> Heat, flames, ignition sources, and incompatibles	<b>Incompatibility (Materials to Avoid):</b> Oxidizing agents, i.e. hydrogen peroxide, Nitric Acid, Perchloric Acid, Perchloric Acid, Chromium Trioxide  <b>Hazardous Polymerization:</b> Will not occur
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Section 11: Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - Skin	Irritation - Eye
Mouse: LD50 = 3600 mg/kg;	N/DA	Rat=1030 ug/m3/16W	Skin, rabbit:LD50= 12800 mg/kg.	N/DA
Sensitization	Mutagenicity	Sub-chronic Toxicity		
N/DA	Rat=1030 ug/m3/16W	N/DA		

## Section 12: Ecological Information

### Ecotoxicological Information:

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
The LC50/96-hour values for fish are over 100mg/l.	N/ DA	N/ DA	N/ DA	N/ DA

### Chemical Fate Information

<b>Biodegradability</b>	When released into the soil, this material is expected to quickly evaporate. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade extent. When released to water, this material is expected to quickly evaporate. When released into water, this material is expected to have a half-life between 1 and 10 days. When released into water, this material may biodegrade to a moderate extent. This material is not expected to significantly bioaccumulate.
<b>Chemical Oxygen Demand</b>	N/ DA

### Section 13: Disposable Considerations

Dispose of diking materials and absorbent in compliance with State, Local and Federal regulations. Residual vapors may explode on ignition, do not cut, drill or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

### Section 14: Transport Information

<b>DOT (49 CFR 172)</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Identification Number:	UN1993
Marine Pollutant:	No
Special Provisions:	T8, T31
<b>Emergency Response Guidebook (ERG) #:</b>	<b>128</b>
<b>IATA (DGR):</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Class or Division:	3
UN or ID Number:	UN1993
Packaging Instructions:	
<b>Emergency Response Guidebook (ICAO #):</b>	
<b>IMO (IMDG):</b>	
Proper Shipping Name:	UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PG11
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation:	None
<b>Emergency Schedule (EmS) #:</b>	
<b>Other Information:</b>	<b>Flash Point = 20°C</b>

### Section 15: Regulatory Information

#### US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following (HAP's) or ODS: • NONE
Clean Water Act: Priority Pollutant	The following ingredients are listed as hazardous pollutants under the CWA: • Isobutyl Acetate, CAS# 110-19-0 None of the ingredients are listed as primary pollutants nor are they listed as toxic pollutants.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food-packaging additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSA Hazard Communication Standard. Its hazards are: • Immediate (acute) health hazard • Fire hazard
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): • Ethyl Acetate CAS# 141-78-6, RCRA Code: U112 • Characteristic of Ignitability, RCRA Code: D001
SARA Title III: Section 302	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA title III: Section 304	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): • Ethyl Acetate CAS# 141-78-6, RQ (Lbs) 5000 • Isobutyl Acetate, CAS# 110-19-0, RQ (Lbs) 5000
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: • Immediate (acute) health hazard • Fire hazard
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting requirements of Section 313 Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: • Isopropyl Alcohol CAS# 67-63-0
TSCA Section 8(b): Inventory	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.

#### State Regulations


CA Right-to Know- Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
NJ Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.



PA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
FL Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.
MN Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.

<b>International Regulations</b>	
CDSL: Canadian Inventory Transitional List)	(on Canadian Ethyl Acetate CAS# 141-78-6, Isopropyl Alcohol CAS# 67-63-0, Isobutyl Acetate CAS# 110-19-0.

**Labeling according to EC Directives - 1999/45/EC**


European Community:	<b>B-2 Nail Prep Primer:</b>
	<ul style="list-style-type: none"> <li>HAZARD SYMBOLS: <b>Xn, F:</b> harmful, <i>Highly Flammable</i></li> </ul>
	<ul style="list-style-type: none"> <li>RISK PHRASES: <b>R11:</b> <i>highly flammable</i>, <b>R20/22:</b> <i>Harmful by inhalation and if swallowed</i>, <b>R36/37/38:</b> <i>Irritating to eyes, respiratory system and skin</i></li> </ul>
	<ul style="list-style-type: none"> <li>SAFETY PHRASES: <b>S7/9:</b> <i>keep container tightly closed and in a well ventilated place</i>, <b>S16:</b> <i>keep away from sources of ignition-no smoking</i>, <b>S24/25:</b> <i>avoid contact with skin and eyes</i>, <b>S33:</b> <i>take precautionary measures against static discharges</i>, <b>S37/39:</b> <i>wear suitable gloves and eye/face protection</i>, <b>S45:</b> <i>In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible)</i></li> </ul>

**Section 16: Other Information**


<b>EU Classes and Risk / Safety Phrases for Referenced ingredients ( See Section 2):</b>
F-Flammable substance or preparations
Xi-Irritants
<b>Risks Phrases:</b>
R11- Highly flammable; R36-Irritating to eyes; R66-Repeated exposure may cause skin dryness or cracking; R67- Vapors may cause drowsiness and dizziness
<b>Safety Phrases:</b>
S2 Keep out of reach of children; S7 Keep container tightly closed; S16 Keep away from sources of ignition-No Smoking;
S23 Do not breathe gas/fumes/vapor/spray S24/25 Avoid contact with skin and eyes; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S29 Do not empty into drains; S33 Take precautionary measures against static discharges

**Hazard Rating System (Pictograms)**

**NFPA:**



**HMIS:**



Revised Sections Since Last Verion:	NONE
-------------------------------------	------

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or exprense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Systems at 1(800) 535-5053.